

lished requirements, including but not limited to, the ordinance codified in this chapter, other ordinances and resolutions, the Director of Public Works shall issue an order specifying such nuisance, violations, or threatened violations, and ordering compliance within the time schedule specified therein.

B. Noncompliance with such order shall constitute a violation of this chapter. (Ord. 322 § 1, 1976).

**13.08.415 Implementing provisions – Serious and immediate hazards.**

Notwithstanding the provisions of any other section of this chapter, whenever in the judgment of the Director of Public Works it appears that any waste discharge has an adverse affect on the life, health or safety of any person, or to the sewer system, the Director of Public Works is empowered to terminate service immediately. (Ord. 322 § 1, 1976).

**13.08.420 Implementing provisions – Maintenance of pretreatment facilities.**

Where pretreatment facilities are provided for any waters or wastes, they shall be maintained continuously in satisfactory and effective operation by the owner at the owner's expense and to the satisfaction of the City. (Ord. 322 § 1, 1976).

**13.08.425 Implementing provisions – Traps and interceptors required.**

A. Grease, oil, sand traps and interceptors shall be provided for the following business or processes:

1. Restaurants;
2. Carwashes;
3. Breweries;
4. Mud baths;
5. Bottling plants.

In addition to those businesses or processes listed above, suspended solids that meet the criteria of CMC 13.08.335 shall be removed prior to entering the sewer system, except that such traps or interceptors shall not be required for buildings used for residential purposes.

B. All traps and interceptors shall be of a type and capacity designated by the Uniform Plumbing Code (UPC), and shall be located as to be readily and easily accessible for cleaning and inspection. Other traps and/or interceptors may be used as per Section 201(E) of the UPC. In existing facilities where it can be proven by the owner that the size of trap or interceptor required by the UPC cannot be

installed based on unreasonable hardship or if an existing system can be shown to be effective, a smaller capacity grease trap may be installed if the owner implements a daily monitoring program. The duration of the daily monitoring program shall be for a period of one month or until the trap has been cleaned four times. The data obtained from the monitoring program shall be recorded and used to establish a maintenance schedule. The data and maintenance schedule shall be submitted to the Department of Public Works for approval. (Ord. 462, 1991; Ord. 322 § 1, 1976).

**13.08.430 Implementing provisions – Maintenance of traps and interceptors.**

All grease, oil, sand traps and interceptors shall be maintained by the owner, at the owner's expense, in continuously efficient operation at all times. Any chemicals, bacteria or enzymes used in the treatment of grease shall be approved by the Director of Public Works. The owner shall keep maintenance records. The maintenance records shall contain the following information: when the trap or interceptor was cleaned, how much grease was removed, how much and when any pretreatment was used. The grease shall be disposed of to a licensed grease/oil recycling firm. Other methods of grease disposal may be used if first approved by the Department of Public Works. The method of disposal shall be verified by invoice and be kept with the maintenance records. Maintenance records shall be maintained on the premises and be available for inspection by a representative of the City. The City shall make at least one unannounced inspection a year to verify compliance with the above requirements. (Ord. 462, 1991; Ord. 322 § 1, 1976).

**13.08.432 Inspection and permit fees.**

Permit fees and inspections shall be required as adopted by the City and the UPC, except that for existing businesses permit fees shall be waived if the installation is performed by a licensed plumber. Permit applications shall be submitted with grease trap/interceptor sizing calculations. (Ord. 462, 1991).

**13.08.435 Implementing provisions – Measurements and tests.**

A. All measurements, tests and analyses of the characteristics of waters and wastes to which reference is made in this chapter shall be determined in accordance with the latest edition of "Standard Methods for the Examination of Water and Waste-

lished requirements, including but not limited to, the ordinance codified in this chapter, other ordinances and resolutions, the Director of Public Works shall issue an order specifying such nuisance, violations, or threatened violations, and ordering compliance within the time schedule specified therein.

B. Noncompliance with such order shall constitute a violation of this chapter. (Ord. 322 § 1, 1976).

**13.08.415 Implementing provisions – Serious and immediate hazards.**

Notwithstanding the provisions of any other section of this chapter, whenever in the judgment of the Director of Public Works it appears that any waste discharge has an adverse affect on the life, health or safety of any person, or to the sewer system, the Director of Public Works is empowered to terminate service immediately. (Ord. 322 § 1, 1976).

**13.08.420 Implementing provisions – Maintenance of pretreatment facilities.**

Where pretreatment facilities are provided for any waters or wastes, they shall be maintained continuously in satisfactory and effective operation by the owner at the owner's expense and to the satisfaction of the City. (Ord. 322 § 1, 1976).

**13.08.425 Implementing provisions – Traps and interceptors required.**

A. Grease, oil, sand traps and interceptors shall be provided for the following business or processes:

1. Restaurants;
2. Carwashes;
3. Breweries;
4. Mud baths;
5. Bottling plants.

In addition to those businesses or processes listed above, suspended solids that meet the criteria of CMC 13.08.335 shall be removed prior to entering the sewer system, except that such traps or interceptors shall not be required for buildings used for residential purposes.

B. All traps and interceptors shall be of a type and capacity designated by the Uniform Plumbing Code (UPC), and shall be located as to be readily and easily accessible for cleaning and inspection. Other traps and/or interceptors may be used as per Section 201(E) of the UPC. In existing facilities where it can be proven by the owner that the size of trap or interceptor required by the UPC cannot be

installed based on unreasonable hardship or if an existing system can be shown to be effective, a smaller capacity grease trap may be installed if the owner implements a daily monitoring program. The duration of the daily monitoring program shall be for a period of one month or until the trap has been cleaned four times. The data obtained from the monitoring program shall be recorded and used to establish a maintenance schedule. The data and maintenance schedule shall be submitted to the Department of Public Works for approval. (Ord. 462, 1991; Ord. 322 § 1, 1976).

**13.08.430 Implementing provisions – Maintenance of traps and interceptors.**

All grease, oil, sand traps and interceptors shall be maintained by the owner, at the owner's expense, in continuously efficient operation at all times. Any chemicals, bacteria or enzymes used in the treatment of grease shall be approved by the Director of Public Works. The owner shall keep maintenance records. The maintenance records shall contain the following information: when the trap or interceptor was cleaned, how much grease was removed, how much and when any pretreatment was used. The grease shall be disposed of to a licensed grease/oil recycling firm. Other methods of grease disposal may be used if first approved by the Department of Public Works. The method of disposal shall be verified by invoice and be kept with the maintenance records. Maintenance records shall be maintained on the premises and be available for inspection by a representative of the City. The City shall make at least one unannounced inspection a year to verify compliance with the above requirements. (Ord. 462, 1991; Ord. 322 § 1, 1976).

**13.08.432 Inspection and permit fees.**

Permit fees and inspections shall be required as adopted by the City and the UPC, except that for existing businesses permit fees shall be waived if the installation is performed by a licensed plumber. Permit applications shall be submitted with grease trap/interceptor sizing calculations. (Ord. 462, 1991).

**13.08.435 Implementing provisions – Measurements and tests.**

A. All measurements, tests and analyses of the characteristics of waters and wastes to which reference is made in this chapter shall be determined in accordance with the latest edition of "Standard Methods for the Examination of Water and Waste-